



## Manguito de fijación HE2320-SKF

### HE2320-SKF



H, HA, HE, HE .. B



HA .. E, HE .. E, HA .. EL, HE .. EL, HE .. BE

| Principal dimensions |     |       |       |    |       |        | Mass | Designations<br>Adaptor sleeve with<br>nut and locking<br>device | Appertaining<br>lock nut | Appro-<br>priate<br>locking<br>device | Appro-<br>priate<br>hydraulic<br>nut |
|----------------------|-----|-------|-------|----|-------|--------|------|------------------------------------------------------------------|--------------------------|---------------------------------------|--------------------------------------|
| $d_1$                | $d$ | $d_2$ | $R_1$ | B  | $R_2$ | G      |      |                                                                  |                          |                                       |                                      |
| in./mm               | mm  |       |       |    |       |        | kg   | -                                                                |                          |                                       |                                      |
| 2 1/2<br>65,9        | 100 | 130   | 97    | 18 | 20    | M100x2 | 2,2  | HE 2320                                                          | KM 20                    | MB 20                                 | HMV 20E                              |



**Manguito de fijación HE2320-SKF**

| <b>Caractéristique</b> | <b>Valeur</b> |
|------------------------|---------------|
| Longitud (mm)          | 97            |
| dA - Diámetro del eje  | 88,9          |
| Marca                  | SKF           |
| Diámetro sobre tuerca  | 130           |
| Unidad de venta        | pieza         |

