

Casquillo de bolas KB20-INA

KB20-INA

LE BON ROULEMENT

Tableau de dimensions (en mm)

Désignation			Masse m	Dimensions			Cotes adjacentes			
				F _w	D	L	B ₂	L ₂	B ₁₂	
					h5	h12				
				Tolérances						
KB20	KB20-PP	KB20-PP-AS	90	20	+0,008 -0,002	32	45	-	31,2	1,6
KB320	KB320-PP	KB320-PP-AS	70					10		
KB020	KB020-PP	KB020-PP-AS	70							

B ₁	D _n	T ₁	N _L	N ₂	n	β	Rangées de billes Nombre	Charges de base			
								dyn. C _{0 min} N	stat. C _{0 max} N	dyn. C _{max} N	stat. C _{0 max} N
-		-	-	2	-	-	4	1 570	1 230	1 660	1 570
3	30,3										
-		1,2	2,2		60	52	5	-	-	1 600	1 280



Casquillo de bolas KB20-INA

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	32
C - Espesor (mm)	45
Marca	INA
Tipo del rodamiento	Casquillo de bolas
Tipo de sellado	No estanco
Rodamiento serie	KB - LME
Unidad de venta	pieza

