

Casquillo de bolas KBS40-P-INA

KBS40-P-INA

LE BON ROULEMENT

Tableau de dimensions (en mm)

Désignation			Masse m	Dimensions			Cotes adjacentes		
				F _d	D	L	B ₂	L ₂	B ₁₂
					h5	H12		H13	
				Tolérances					
KB40	KB40-PP	KB40-PP-AS	600	40	-0,011 -0,002	62	90	-	60,3 2,15
KBS40	KBS40-PP	KBS40-PP-AS						18,2	
KBO40	KBO40-PP	KBO40-PP-AS	520						

B ₁	D _n	T ₁	N _L	N ₂	n	β	Rangée de billes Nombre	Charges de base			
								dyn. C _{0 max} N	stat. C _{0 max} N	dyn. C _{max} N	stat. C _{max} N
-	-	-	-	3	-	-	6	6 000	4 400	6 400	5 600
3	SP	-	-	-	54	54	5	-	-	6 100	4 600



Casquillo de bolas KBS40-P-INA

Caractéristique	Valeur
d - Diámetro interior (mm)	40
D - Diámetro exterior (mm)	62
C - Espesor (mm)	80
Marca	INA
Tipo del rodamiento	Casquillo de bolas
Tipo de sellado	Simple estanco plástico (RS, RS1, DU, LU, E)
Rodamiento serie	KBS - LME
Unidad de venta	pieza

