

Casquillo de agujas YB47-IKO

YB47-IKO





BA...Z BHA...Z BAM...Z YB

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end Min. (Ref.) g	Standard	Mass (Ref.) g	Closed end Min. (Ref.) g	Mass (Ref.) g	Grease retained Min. (Ref.) g	Mass (Ref.) g	
6.350 (¹ / ₄)	BA 44	2.1	—	—	—	—	—	—	—	
	BA 45 Z	2.5	BAM 45	2.7	—	—	—	—	—	
	BA 47 Z	3.5	BAM 47	3.7	—	—	—	—	—	
	—	—	—	—	—	—	—	YB 45	3.2	
—	—	—	—	—	—	—	—	YB 47	4.6	

Boundary dimensions - mm (inch)				Standard mounting dimensions - mm				Ball diam. tolerance C ₁		Ball diam. tolerance C ₂		Allowable rotational speed ¹⁾ rpm	Assembled inner ring
F ₀	D	C	f ₂ Max.	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	N	N				
6.350 (¹ / ₄)	11.112 (⁷ / ₁₆)	6.351 (250)	1	—	—	—	—	1.770	1.390	55 000	—	—	
6.350 (¹ / ₄)	11.112 (⁷ / ₁₆)	7.921 (312)	1	—	—	—	—	1.510	1.120	55 000	—	—	
6.350 (¹ / ₄)	11.112 (⁷ / ₁₆)	11.131 (436)	1	6.350	6.341	11.122	11.104	2.650	2.310	55 000	—	—	
6.350 (¹ / ₄)	11.112 (⁷ / ₁₆)	7.921 (312)	—	—	—	—	—	4.450	4.670	25 000	—	—	
6.350 (¹ / ₄)	11.112 (⁷ / ₁₆)	11.131 (436)	—	—	—	—	—	6.320	7.650	25 000	—	—	



Casquillo de agujas YB47-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	6,35
D - Diámetro exterior (mm)	1,11
C - Espesor (mm)	11,13
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

