

Casquillo de agujas YB78-IKO

YB78-IKO





BA...Z BHA...Z BAM BHAM YB

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Gross retained	Mass (Ref.) g
11,112 ($\frac{7}{16}$)	BA 76 Z	4.8	BAM 76	5.3	—	—	—	—	—	—
	BA 77 Z	5.5	BAM 77	6.2	—	—	—	—	—	—
	BA 78 Z	6.4	BAM 78	7	—	—	—	—	—	—
	BA 710 Z	7.9	BAM 710	8.5	—	—	—	—	—	—
	—	—	—	—	—	—	—	—	YB 78	8.2

Boundary dimensions mm (inch)				Standard bearing dimensions mm				Basic load rating	Basic load rating	Allowable	Assembled
F_w	D	C	f_2	Shaft dia. h6		Housing bore dia. J7		C	C_0	rotational speed ⁽¹⁾ rpm	(inner ring)
			Max	Max	Min	Max	Min	N	N		
11,112	15.875	9.52(3.75)	1					3 290	3 470	35 000	—
11,112	15.875	11.13(4.38)	1					4 150	4 690	35 000	—
11,112	15.875	12.70(5.00)	1	11,112	11,101	15.885	15.867	4 460	5 130	35 000	—
11,112	15.875	15.88(6.25)	1					6 020	7 550	35 000	—
11,112	15.875	12.70(5.00)	—					10 100	15 900	14 000	—



Casquillo de agujas YB78-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	11,11
D - Diámetro exterior (mm)	15,88
C - Espesor (mm)	12,7
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

