


Casquillo de agujas YB84-IKO

YB84-IKO

LE BON
ROULEMENT



BA...Z BHA...Z

BAM BHAM

YB

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Gross retained	Mass (Ref.) g
12.700 (1/2")	—	—	—	—	—	—	—	—	YB 84	4.3
	—	—	—	—	—	—	—	—	YB 86	6.7
	—	—	—	—	—	—	—	—	YB 87	7.9
	—	—	—	—	—	—	—	—	YB 88	9.1
	—	—	—	—	—	—	—	—	YB 810	11.5
	—	—	—	—	—	—	—	—	YB 812	13.9

Boundary dimensions mm (inch)				Standard bearing dimensions mm				Basic static load rating C_0	Basic dynamic load rating C_1	Allowable rotational speed ⁽¹⁾	Assembled (inner ring)
F_w	D	C	f_1	Shaft dia. h6	Housing bore dia. J7	C'	C_0	N	N	rpm	
12.700 / $\frac{1}{2}$	17.462 / $\frac{5}{8}$	6.350 / 2501	—	—	—	—	—	5 260	7 150	12 000	—
12.700 / $\frac{1}{2}$	17.462 / $\frac{5}{8}$	9.520 / 3751	—	—	—	—	—	8 150	12 600	12 000	—
12.700 / $\frac{1}{2}$	17.462 / $\frac{5}{8}$	11.130 / 4381	—	12.700	12.689	17.472	17.454	9 530	15 300	12 000	—
12.700 / $\frac{1}{2}$	17.462 / $\frac{5}{8}$	12.700 / 5001	—	—	—	—	—	10 800	18 100	12 000	YB 84
12.700 / $\frac{1}{2}$	17.462 / $\frac{5}{8}$	15.880 / 6251	—	—	—	—	—	13 400	23 700	12 000	—
12.700 / $\frac{1}{2}$	17.462 / $\frac{5}{8}$	19.050 / 7501	—	—	—	—	—	15 800	29 300	12 000	—



Casquillo de agujas YB84-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	12,7
D - Diámetro exterior (mm)	17,46
C - Espesor (mm)	6,35
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

