

Casquillo de agujas YB86-IKO

YB86-IKO

**LE BON
ROULEMENT**

BA...Z BHA...Z

BAM BHAM

YB

Shaft dia. mm (inch)	Identification number							
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g
12,700 ($\frac{1}{2}$)	—	—	—	—	—	—	—	YB 84 4.3
	—	—	—	—	—	—	—	YB 86 6.7
	—	—	—	—	—	—	—	YB 87 7.9
	—	—	—	—	—	—	—	YB 88 9.1
	—	—	—	—	—	—	—	YB 810 11.5
	—	—	—	—	—	—	—	YB 812 13.9

Boundary dimensions mm (inch)				Standard bearing dimensions mm				Basic load rating C_0 N	Basic load rating C_1 N	Allowable rotational speed ¹⁾ rpm	Assembled inner ring
F_w	D	C	f_1 Max	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	C' Max. Min.					
12,700 ($\frac{1}{2}$)	17,462 ($\frac{5}{8}$)	6,350, 2501	—	—	—	—	5 260	7 150	12 000	—	
12,700 ($\frac{1}{2}$)	17,462 ($\frac{5}{8}$)	9,520, 3751	—	—	—	—	8 150	12 600	12 000	—	
12,700 ($\frac{1}{2}$)	17,462 ($\frac{5}{8}$)	11,130, 4381	—	12,700	12,689	17,472	9 530	15 300	12 000	—	
12,700 ($\frac{1}{2}$)	17,462 ($\frac{5}{8}$)	12,700, 5001	—	—	—	—	10 800	18 100	12 000	—	
12,700 ($\frac{1}{2}$)	17,462 ($\frac{5}{8}$)	15,880, 6251	—	—	—	—	13 400	23 700	12 000	—	
12,700 ($\frac{1}{2}$)	17,462 ($\frac{5}{8}$)	19,050, 7501	—	—	—	—	15 800	29 300	12 000	—	



Casquillo de agujas YB86-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	12,7
D - Diámetro exterior (mm)	17,46
C - Espesor (mm)	9,52
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

