

Casquillo de agujas YB87-IKO

YB87-IKO





Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
12.700 (1/2")	—	—	—	—	—	—	—	—	YB 84	4.3
	—	—	—	—	—	—	—	—	YB 86	6.7
	—	—	—	—	—	—	—	—	YB 87	7.9
	—	—	—	—	—	—	—	—	YB 88	9.1
	—	—	—	—	—	—	—	—	YB 810	11.5
	—	—	—	—	—	—	—	—	YB 812	13.9

Boundary dimensions mm (inch)				Standard housing dimensions mm				Basic static load rating C ₀		Basic dynamic load rating C ₁₀		Allowable rotational speed ¹⁾ rpm	Assembled (inner ring)
F _{wh}	D	C	$\frac{f_1}{2}$ Max	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	C ₀	C ₁₀	N	N				
12.700 / 1/2	17.462 5/32	6.350 2501	—	—	—	—	—	5 260	7 150	12 000	—	—	
12.700 / 1/2	17.462 5/32	9.525 3751	—	—	—	—	—	8 150	12 600	12 000	—	—	
12.700 / 1/2	17.462 5/32	11.130 4381	—	12.700	12.689	17.472	17.454	9 530	15 300	12 000	—	—	
12.700 / 1/2	17.462 5/32	12.700 5001	—	—	—	—	—	10 800	18 100	12 000	—	—	
12.700 / 1/2	17.462 5/32	15.880 6251	—	—	—	—	—	13 400	23 700	12 000	—	—	
12.700 / 1/2	17.462 5/32	19.050 7501	—	—	—	—	—	15 800	29 300	12 000	—	—	



Casquillo de agujas YB87-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	12,7
D - Diámetro exterior (mm)	17,46
C - Espesor (mm)	11,13
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

