


Casquillo de agujas YB88-IKO

YB88-IKO

LE BON
ROULEMENT



BA...Z BHA...Z BAM BHAM YB

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Gross retained	Mass (Ref.) g
12.700 ($\frac{1}{2}$)	—	—	—	—	—	—	—	—	YB 84	4.3
	—	—	—	—	—	—	—	—	YB 86	6.7
	—	—	—	—	—	—	—	—	YB 87	7.9
	—	—	—	—	—	—	—	—	YB 88	9.1
	—	—	—	—	—	—	—	—	YB 810	11.5
	—	—	—	—	—	—	—	—	YB 812	13.9

Boundary dimensions mm (inch)				Standard bearing dimensions mm				Basic load rating (C _r)	Basic load rating (C ₀)	Allowable rotational speed ⁽¹⁾	Assembled (inner ring)
F _w	D	C	f ₁ Max	Shaft dia. h6		Housing bore dia. J7		N	N	rpm	
				Max	Min	Max	Min				
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	6.350 (250)	—	—	—	—	—	5 200	7 150	12 000	—
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	9.520 (375)	—	—	—	—	—	8 150	12 600	12 000	—
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	11.130 (438)	—	12.700	12.689	17.472	17.454	9 530	15 300	12 000	—
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	12.700 (500)	—	—	—	—	—	10 800	18 100	12 000	YB 88
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	15.880 (625)	—	—	—	—	—	13 400	23 700	12 000	—
12.700 ($\frac{1}{2}$)	17.462 ($\frac{9}{16}$)	19.050 (750)	—	—	—	—	—	15 800	29 300	12 000	—



Casquillo de agujas YB88-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	12,7
D - Diámetro exterior (mm)	17,46
C - Espesor (mm)	12,7
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

