

Casquillo de agujas YB98-IKO
YB98-IKO





Shaft dia. mm (inch)	Identification number							
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g
14.288 ($\frac{11}{16}$)	---	---	---	---	---	---	---	---
								YB 98 10.1
								YB 910 12.7
								YB 912 15.4

Boundary dimensions mm (inch)				Standard bearing dimensions mm				Basic load rating	Basic load rating	Allowable	Assembled
F_w	D	C	f_2	Shaft dia. h6		Housing bore dia. J7		C	C_0	rotational speed ⁽¹⁾	(inner ring)
			Max	Max	Min	Max	Min	N	N	rpm	
14.288 $\frac{11}{16}$	19.050 $\frac{3}{4}$	12.701 $\frac{1}{2}$	---					11 600	20 400	11 000	IRB 68
14.288 $\frac{11}{16}$	19.050 $\frac{3}{4}$	15.881 $\frac{5}{8}$	---					14 300	26 700	11 000	---
14.288 $\frac{11}{16}$	19.050 $\frac{3}{4}$	19.051 $\frac{3}{4}$	---					16 800	33 000	11 000	IRB 612



Casquillo de agujas YB98-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	14,29
D - Diámetro exterior (mm)	19,05
C - Espesor (mm)	12,7
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

