

Casquillo de agujas YB124-IKO

YB124-IKO





Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
19,050 (3/4")	—	—	—	—	—	—	—	YB 124	8.5
	—	—	—	—	—	—	—	YB 128	17.8
	—	—	—	—	—	—	—	YB 1210	22.5
	—	—	—	—	—	—	—	YB 1212	27

Boundary dimensions mm (inch)				Standard mounting dimensions mm				Ball diam. ball ring C	Ball diam. inner ring C ₃	Allowable rotational speed ¹⁾	Assembled inner ring
F ₀	D	C	J ₂ Max	Shaft dia. H8 Max. Min.	Housing bore dia. J7 Max. Min.			N	N	rpm	
19,050 J ₆	25,400 J	6,35 J ₆	252	—	—	—	—	7 820	10 230	8 000	—
19,050 J ₆	25,400 J	12,70 J ₆	589	—	—	—	—	16 600	26 900	8 000	IRB 88-1
19,050 J ₆	25,400 J	15,88 J ₆	825	—	—	—	—	20 500	35 300	8 000	IRB 810-1
19,050 J ₆	25,400 J	19,05 J ₆	790	19,050	19,037 25,412 25,391	—	—	24 100	43 400	8 000	IRB 812-1



Casquillo de agujas YB124-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	19,05
D - Diámetro exterior (mm)	25,4
C - Espesor (mm)	6,35
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

