

Casquillo de agujas YBH1310-IKO

YBH1310-IKO

**LE BON
ROULEMENT**

BA...Z BHA...Z

BAM BHAM

YB

Shaft dia. mm (inch)	Identification number							
	Standard	Mass (Ref.) g	Crossed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Crossed end	Mass (Ref.) g
20.638 ($\frac{11}{16}$)	—	—	—	—	BHA 138 Z	20	BHAM 138	22.5
	—	—	—	—	BHA 1310 Z	23.5	BHAM 1310	25.5
	—	—	—	—	BHA 1312 Z	28.5	BHAM 1312	30.5
	—	—	—	—	—	—	—	—
	—	—	—	—	—	—	—	—
							YBH 1310	30.5
							YBH 1312	37

Boundary dimensions - mm (inch)				Standard mounting dimensions - mm				Shaft diam. mm	Housing bore dia. mm	Ball diam. mm	Ball race diam. mm	Allowable rotational speed ¹⁾ rpm	Assembled inner ring
F_n	D	C	$\frac{B}{2}$	Shaft dia. mm	Housing bore dia. mm	Ball diam. mm	Ball race diam. mm	N	N	N	N		
20.638 $\frac{5}{16}$	20.575 $\frac{1}{2}$	12.701 $\frac{500}{100}$	1.3	20.638	20.625	28.587	28.586	9 500	11 200	19 000	IRB 98		
20.638 $\frac{5}{16}$	20.575 $\frac{1}{2}$	15.881 $\frac{625}{100}$	1.3					13 800	18 200	19 000	IRB 910		
20.638 $\frac{5}{16}$	20.575 $\frac{1}{2}$	19.051 $\frac{750}{100}$	1.3					17 300	24 400	19 000	IRB 912		
20.638 $\frac{5}{16}$	20.575 $\frac{1}{2}$	15.881 $\frac{625}{100}$	1.3					22 900	36 300	7 500	IRB 910		
20.638 $\frac{5}{16}$	20.575 $\frac{1}{2}$	19.051 $\frac{750}{100}$	1.3					27 200	46 300	7 500	IRB 912		



Casquillo de agujas YBH1310-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	20,64
D - Diámetro exterior (mm)	28,58
C - Espesor (mm)	15,88
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

