

Casquillo de agujas YBH1312-IKO

YBH1312-IKO



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Groove retained	Mass (Ref.) g
20.638 ($\frac{11}{16}$)	—	—	—	—	BHA 138 Z	20	BHAM 138	22.5	—	—
	—	—	—	—	BHA 1310 Z	23.5	BHAM 1310	25.5	—	—
	—	—	—	—	BHA 1312 Z	28.5	BHAM 1312	30.5	—	—
	—	—	—	—	—	—	—	—	YBH 1310	30.5
									YBH 1312	37

Boundary dimensions mm (inch)				Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ¹⁾	Assembled inner ring
F _w	D	C	f ₂ Max	Shaft dia. h8 Max. Min.	Housing bore dia. j7 Max. Min.	Shaft dia. h8 Max. Min.	Housing bore dia. j7 Max. Min.	N	N	rpm	
20.638 $\frac{5}{16}$	28.575 $\frac{1}{1}$	12.70 $\frac{1}{2}$	1.3					9 500	11 200	19 000	IRB 98
20.638 $\frac{5}{16}$	28.575 $\frac{1}{1}$	15.88 $\frac{5}{8}$	1.3					13 800	18 200	19 000	IRB 910
20.638 $\frac{5}{16}$	28.575 $\frac{1}{1}$	19.05 $\frac{3}{4}$	1.3	20.638	20.625	28.587	28.588	17 300	24 400	19 000	IRB 912
20.638 $\frac{5}{16}$	28.575 $\frac{1}{1}$	15.88 $\frac{5}{8}$	—					22 900	36 300	7 500	IRB 910
20.638 $\frac{5}{16}$	28.575 $\frac{1}{1}$	19.05 $\frac{3}{4}$	—					27 200	45 300	7 500	IRB 912



Casquillo de agujas YBH1312-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	20,64
D - Diámetro exterior (mm)	28,58
C - Espesor (mm)	19,05
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

