

Casquillo de agujas YB1612-IKO

YB1612-IKO

BA...Z BHA...Z
BAM BHM
YB

Identification number									
Shaft dia. mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
25.400 (1)	—	—	—	—	—	—	—	—	YB 168 23
	—	—	—	—	—	—	—	—	YB 1612 34.5
	—	—	—	—	—	—	—	—	YB 1616 46.5

Boundary dimensions mm (inch)			Standard mounting dimensions mm			Basic load rating C	Basic load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _a	D	C	d ₁ Max.	Shaft dia. H6 Min.	Housing bore dia. J7 Min.	N	N	rpm	
25.400-1	31.750 (1 1/4)	12.700 (500)	—	—	—	19 400	36 000	6 000	IRB 128
25.400-1	31.750 (1 1/4)	19.050 (750)	—	—	—	28 200	58 000	6 000	IRB 1212
25.400-1	31.750 (1 1/4)	25.400 (1 000)	—	—	—	36 300	80 300	6 000	IRB 1216



Casquillo de agujas YB1612-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	25,4
D - Diámetro exterior (mm)	31,75
C - Espesor (mm)	19,05
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

