

Casquillo de agujas YB248-IKO

YB248-IKO

LE BON ROULEMENT

BA...Z BHA...Z

BAM BHAM

YB

Identification number									
Shaft dia. mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
38.100 (1 1/2)	---	---	---	---	---	---	---	---	---
									YB 246 38
									YB 248 51.5
									YB 2414 91
									YB 2416 106
									YB 2420 131

Boundary dimensions mm (inch)				Standard mounting dimensions mm				Basic rated load	Basic rated load	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
F_w	D	C	r_1	Shaft dia. H8		Housing bore dia. H7		C_0	C_0		
38.100 (1 1/2)	47.625 (1 7/8)	9.521 (.375)	---	Max.	Min.	Max.	Min.	21 000	34 100	4 000	---
38.100 (1 1/2)	47.625 (1 7/8)	12.701 (.500)	---					28 700	50 900	4 000	---
38.100 (1 1/2)	47.625 (1 7/8)	22.221 (.875)	---	38.100	38.084	47.639	47.614	48 900	101 000	4 000	IRB 2014
38.100 (1 1/2)	47.625 (1 7/8)	25.401 (1.000)	---					55 100	118 000	4 000	IRB 2016
38.100 (1 1/2)	47.625 (1 7/8)	31.751 (1.250)	---					66 800	151 000	4 000	IRB 2020



Casquillo de agujas YB248-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	38,1
D - Diámetro exterior (mm)	47,63
C - Espesor (mm)	12,7
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

