

Casquillo de agujas YB2414-IKO

YB2414-IKO

**LE BON
ROULEMENT**

BA...Z BHA...Z

BAM BHAM

YB

Identification number									
Shaft dia. mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained
38.100 (1 1/2)	---	---	---	---	---	---	---	---	YB 246
	---	---	---	---	---	---	---	---	38
	---	---	---	---	---	---	---	---	YB 248
	---	---	---	---	---	---	---	---	51.5
	---	---	---	---	---	---	---	---	YB 2414
---	---	---	---	---	---	---	---	---	91
	---	---	---	---	---	---	---	---	YB 2416
	---	---	---	---	---	---	---	---	106
---	---	---	---	---	---	---	---	---	YB 2420
---	---	---	---	---	---	---	---	---	131

Boundary dimensions mm (inch)				Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ¹⁾	Assembled inner ring
F_w	D	C	r_1	Shaft dia. H8		Housing bore dia. J7		C	C_0	rpm	
Max.	Max.	Max.	Max.	Max.	Min.	Max.	Min.	N	N		
38.100 (1 1/2)	47.625 (1 7/8)	9.521 (.375)	---	38.100	38.084	47.639	47.614	21 000	34 100	4 000	---
38.100 (1 1/2)	47.625 (1 7/8)	12.701 (.500)	---					28 700	50 900	4 000	---
38.100 (1 1/2)	47.625 (1 7/8)	22.221 (.875)	---					48 900	101 000	4 000	IRB 2014
38.100 (1 1/2)	47.625 (1 7/8)	25.401 (1.000)	---					55 100	118 000	4 000	IRB 2016
38.100 (1 1/2)	47.625 (1 7/8)	31.751 (1.250)	---					66 800	151 000	4 000	IRB 2020



Casquillo de agujas YB2414-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	38,1
D - Diámetro exterior (mm)	47,63
C - Espesor (mm)	22,22
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

