

Casquillo de agujas YB2420-IKO

YB2420-IKO

LE BON ROULEMENT

BA...Z BHA...Z

BAM BHAM

YB

		Identification number							
Shaft dia. mm (inch)		Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g
38.100 (1 1/2)		---	---	---	---	---	---	---	---
									YB 246 38
									YB 248 51.5
									YB 2414 91
									YB 2416 106
									YB 2420 131

Boundary dimensions mm (inch)				Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_a	D	C	r_1	Shaft dia. H8		Housing bore dia. J7		N	N	rpm	
			Max.	Max.	Min.	Max.	Min.				
38.100 (1 1/2)	47.625 (1 7/8)	9.521 (.375)	---	---	---	---	---	21 000	34 100	4 000	---
38.100 (1 1/2)	47.625 (1 7/8)	12.701 (.500)	---	---	---	---	---	28 700	50 900	4 000	---
38.100 (1 1/2)	47.625 (1 7/8)	22.221 (.875)	---	38.100	38.084	47.639	47.614	48 900	101 000	4 000	IRB 2014
38.100 (1 1/2)	47.625 (1 7/8)	25.401 (1.000)	---	---	---	---	---	55 100	118 000	4 000	IRB 2016
38.100 (1 1/2)	47.625 (1 7/8)	31.751 (1.250)	---	---	---	---	---	66 800	151 000	4 000	IRB 2020



Casquillo de agujas YB2420-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	38,1
D - Diámetro exterior (mm)	47,63
C - Espesor (mm)	31,75
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YB
Unidad de venta	pieza

