

Casquillo de agujas YT1715-IKO

YT1715-IKO



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
17	TA 1715 Z TA 1720 Z TA 1725 Z	17.6 23.5 29	TAM 1715 TAM 1720 TAM 1725	18.5 25 31	— — —	— — —	— — —	— — —	— — —	— — —
									YT 1715 YT 1725	29.5 35.5

Boundary dimensions mm			Standard mounting dimensions mm						Basic static load rating C ₀	Basic static load rating C ₁	Allowable rotational speed ¹⁾	Assembled inner ring
F ₀	D	d ₁ Max	Shaft dia. H7		Housing bore dia. H7		H7					
			Max.	Min.	Max.	Min.	Max.	Min.	N	N	rpm	
17	24	1.3	—	—	—	—	—	—	9 000	12 700	25 000	IRT 1215-Z
17	24	1.3	—	—	—	—	—	—	13 900	20 400	25 000	IRT 1220-Z
17	24	1.3	—	—	—	—	—	—	17 900	28 100	25 000	IRT 1225-Z
17	24	1.3	17.000	16.988	24.012	23.991	—	—	16 600	25 000	9 000	IRT 1215-Z
17	24	1.3	—	—	—	—	—	—	27 200	49 000	9 000	IRT 1225-Z



Casquillo de agujas YT1715-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	24
C - Espesor (mm)	15
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YT
Unidad de venta	pieza

