

Casquillo de agujas YT1725-IKO

YT1725-IKO



Shaft dia. mm	Identification number										
	Standard	Mass (Ref. 1) g	Closed end	Mass (Ref. 1) g	Standard	Mass (Ref. 1) g	Closed end	Mass (Ref. 1) g	Grease retained	Mass (Ref. 1) g	
17	TA 1715 Z	17.6	TAM 1715	19.5	—	—	—	—	—	—	
	TA 1720 Z	23.5	TAM 1720	25	—	—	—	—	—	—	
	TA 1725 Z	29	TAM 1725	31	—	—	—	—	—	—	
	—	—	—	—	—	—	—	—	YT 1715	20.5	
									YT 1725	35.5	
Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C _r	Basic static load rating C ₀	Allowable rotational speed ¹⁾	Assembled inner ring
F _w	D	C	h ₂ Max	Shaft dia. h6				N	N	rpm	
				Max.	Min.	Max.	Min.				
17	24	15	1.3	—	—	—	—	9 690	12 700	25 000	WRT 1215-2
17	24	20	1.3	—	—	—	—	13 900	20 400	25 000	WRT 1220-2
17	24	25	1.3	17.050	16.989	24.012	23.991	17 900	26 100	25 000	WRT 1225-2
17	24	15	—	—	—	—	—	16 600	26 000	9 000	WRT 1215-2
17	24	25	—	—	—	—	—	27 200	49 000	9 000	WRT 1225-2



Casquillo de agujas YT1725-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	24
C - Espesor (mm)	25
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YT
Unidad de venta	pieza

