

Casquillo de agujas YT223016-IKO

YT223016-IKO



Shift no.	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
22	TA 223016	26	TAM 223016	29	---	---	---	---	---	---
	TA 223020	32.5	TAM 223020	35.5	---	---	---	---	---	---
	---	---	---	---	---	---	---	---	---	---
	---	---	---	---	---	---	---	---	---	---
									YT 223016	32
									YT 223020	40.5

Boundary dimensions mm				Standard mounting dimensions mm				Ball-point set-screw	Ball-rod set-screw	Ball-rod allowable rotational speed ¹⁾	Assembled inner ring	
F_w	D	C	J_2	Shaft dia. h6		Housing bore dia. H7		C	C_1	N		
				Max.	Min.	Max.	Min.	Max.	Max.	Min.	rpm	
22	30	16	1.3	22.000	21.987	30.012	29.991	—	—	13 200	18 200	18 000
22	30	25	1.3	22.000	21.987	30.012	29.991	—	—	17 500	26 100	18 000
22	30	16	—	—	—	—	—	22 600	38 800	7 000	—	
22	30	20	—	—	—	—	—	28 200	48 900	7 000	—	



Casquillo de agujas YT223016-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	22
D - Diámetro exterior (mm)	30
C - Espesor (mm)	16
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YT
Unidad de venta	pieza

