

Casquillo de agujas YT223020-IKO

YT223020-IKO


**LEBON
ROULEMENT**

TA...Z TLA...Z

TAM TLAM

YT YTL

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
22	TA 223016 Z	26	TAM 223016	29	—	—	—	—	—	—
	TA 223020 Z	32.5	TAM 223020	35.5	—	—	—	—	—	—
	—	—	—	—	—	—	—	—	—	—
	—	—	—	—	—	—	—	—	YT 223016	32
	—	—	—	—	—	—	—	—	YT 223020	40.5

Boundary dimensions mm				Standard mounting dimensions - mm				Ball dynamic load rating C ¹	Ball static load rating C ₀	Allowable rotational speed ¹⁾	Assembled inner ring
F ₀	D	C	J ₂ Max.	Shaft dia. H6 Max. Min.	Housing bore dia. J7 Max. Min.	N7 Max. Min.		N	N	rpm	
22	30	16	1.3	—	—	—	—	13 200	18 200	18 000	IRT 1716-Z
22	30	25	1.3	22.006	21.987	30.012	29.991	17 500	26 100	18 000	IRT 1726-Z
22	30	16	—	—	—	—	—	22 800	36 800	7 000	IRT 1716-Z
22	30	25	—	—	—	—	—	28 200	48 900	7 000	IRT 1726-Z



Casquillo de agujas YT223020-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	22
D - Diámetro exterior (mm)	30
C - Espesor (mm)	20
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YT
Unidad de venta	pieza

