

Casquillo de agujas YT243216-IKO

YT243216-IKO

LE BON
ROULEMENT

TA...Z TLA...Z

TAM TLM

YT YTL

Shaft dia. (mm)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained
24	TA 243216 Z	26	TAM 243216	32	—	—	—	—	—
	TA 243220 Z	26.5	TAM 243220	39	—	—	—	—	—
	—	—	—	—	—	—	—	—	YT 243216
	—	—	—	—	—	—	—	—	34.5
	—	—	—	—	—	—	—	—	YT 243220
	—	—	—	—	—	—	—	—	43.5

Boundary dimensions mm			Standard mounting dimensions mm						Basic dynamic load rating C _N	Basic static load rating C ₀	Allowable rotational speed ¹⁾ rpm	Assembled inner ring
F _w	D	C	Shaft dia. h9		Housing bore dia. H7							
			Max.	Min.	Max.	Min.	Max.	Min.	N	N		
24	32	16	3.4	—	—	—	—	—	14 200	20 500	16 000	IRT 2016
24	32	20	3.4	—	—	—	—	—	18 900	29 400	16 000	IRT 2020
24	32	16	—	24.090	23.987	32.014	31.989	—	23 700	40 100	6 500	IRT 2016
24	32	20	—	—	—	—	—	—	29 900	53 200	6 500	IRT 2020



Casquillo de agujas YT243216-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	24
D - Diámetro exterior (mm)	32
C - Espesor (mm)	16
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YT
Unidad de venta	pieza

