

Casquillo de agujas YT2616-IKO

YT2616-IKO


**LEBON
ROULEMENT**

TA...Z TLA...Z

TAM TLM

YT YTL

Identification number

Shaft dia. mm	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
26	TA 2616 Z TA 2620 Z	30.5 38	TAM 2616 TAM 2620	34.5 42.5	—	—	—	—	—	—
	—	—	—	—	—	—	—	—	YT 2616 YT 2620	37 45.5

Boundary dimensions mm				Standard mounting dimensions - mm				Ball dynamic load rating C'	Ball static load rating C ₀	Allowable rotational speed ¹⁾ rpm	Assembled inner ring	
F _u	D	C	J ₂	Shaft dia. H6 Max.	Min.	Housing bore dia. J7 Max.	Min.	N	N	rpm		
26	34	16	3.4	26.000	25.987	34.014	33.989	—	15 200	22 900	15 000	IRT 2216
26	34	20	3.4	—	—	—	—	20 100	32 800	15 000	15 000	IRT 2220
26	34	16	—	—	—	—	—	24 700	43 300	6 000	6 000	IRT 2216
26	34	20	—	—	—	—	—	30 800	57 500	6 000	6 000	IRT 2220



Casquillo de agujas YT2616-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	26
D - Diámetro exterior (mm)	34
C - Espesor (mm)	16
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YT
Unidad de venta	pieza

