

Casquillo de agujas YT2820-IKO

YT2820-IKO

**LE BON
ROULEMENT**

TA...Z TLA...Z

TAM TLM

YT YTL

Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
26	TA 2620 Z	45	TAM 2620	50	—	—	—	—	—
	TA 2630 Z	67.5	TAM 2630	72.5	—	—	—	—	—
								YT 2620	56.5

Boundary dimensions mm			Standard mounting dimensions mm						Basic static load rating C ₀	Basic dynamic load rating C	Allowable rotational speed ¹⁾ rpm	Assembled inner ring	
F _w	D	C	J ₂	Shaft dia. h6		Housing bore dia. H7		Housing bore dia. k7					
Max.	Max.	Min.	Max.	Max.	Min.	Max.	Min.	Max.	Min.	N	N		
28	37	20	3.4	28.000	27.987	37.014	36.989	—	—	21 200	32 300	13 000	IRT 2230-1
28	37	20	3.4							33 000	56 900	13 000	IRT 2230-1
28	37	20	—							34 700	61 700	8 500	IRT 2220-1



Casquillo de agujas YT2820-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	28
D - Diámetro exterior (mm)	37
C - Espesor (mm)	20
Marca	IKO
Tipo del rodamiento	Casquillo de agujas abierto
Tipo de sellado	No estanco
Rodamiento serie	YT
Unidad de venta	pieza

