

Casquillo de agujas TAMW3845-IKO

TAMW3845-IKO



Shaft dia. mm	Identification number											
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g		
38	TA 3815 Z	51	TAM 3815	60	—	—	—	—	—	—		
	TA 3820 Z	66.5	TAM 3820	74.5	—	—	—	—	—	—		
	TA 3825 Z	82.5	TAM 3825	96	—	—	—	—	—	—		
	TA 3830 Z	104	TAM 3830	114	—	—	—	—	—	—		
	TAMW 3845 Z	149	TAMW 3845	159	—	—	—	—	—	—		
Boundary dimensions mm		Standard mounting dimensions mm						Ball dynamic load rating C _r	Ball static load rating C ₀	Allowable rotational speed ¹⁾ rpm	Assembled inner ring	
F ₀	D	j ₀ mm	Shaft dia. h6		Housing bore dia. H7				N	N	rpm	
			Max.	Min.	Max.	Min.	Max.	Min.				
38	40	15	3.4						19 000	28 000	9 000	IRT 3215-1
38	40	20	3.4						27 700	45 600	9 000	IRT 3220-1
38	40	25	3.4	38.000	37.984	48.014	47.989	—	35 600	63 100	9 000	IRT 3225-1
38	40	30	3.4						43 100	80 600	9 000	IRT 3230-1
38	40	45	3.4						55 700	112 000	9 000	IRT 3245-1



Casquillo de agujas TAMW3845-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	38
D - Diámetro exterior (mm)	48
C - Espesor (mm)	45
Marca	IKO
Tipo del rodamiento	Casquillo de agujas cerrado
Tipo de sellado	No estanco
Especificaciones	Jaula doble
Rodamiento serie	TAM
Unidad de venta	pieza

