

Casquillo de agujas TAMW5545-IKO

TAMW5545-IKO



Shaft dia. mm	Identification number							
	Standard	Mass (Ref. 1) g	Closed end	Mass (Ref. 1) g	Standard	Mass (Ref. 1) g	Closed end	Mass (Ref. 1) g
55	TA 5540 Z 230	---	TAM 5540 250	---	---	---	---	---
55	TAW 5545 Z 250	---	TAMW 5545 270	---	---	---	---	---
55	TAW 5550 Z 280	---	TAMW 5550 300	---	---	---	---	---

Boundary dimensions mm				Standard mounting dimensions - mm								Basic load rating C ₀	Basic load rating C ₁₀	Allowable rotational speed ¹⁾ rpm	Assembled inner ring
F _w	D	C	h ₀ Max.	Shaft dia. h6		Housing bore dia. H7				N	N	N	N	N	N
				Max.	Min.	Max.	Min.	Max.	Min.						
55	67	90	3.4	65.000	64.981	67.018	66.988	---	---	80 000	172 000	5 500	IRT 5540-1	---	---
55	67	45	3.4	---	---	---	---	---	---	79 900	172 000	5 500	IRT 5545-1	---	---
55	67	50	3.4	---	---	---	---	---	---	91 500	205 000	5 500	IRT 5550-1	---	---



Casquillo de agujas TAMW5545-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	55
D - Diámetro exterior (mm)	67
C - Espesor (mm)	45
Marca	IKO
Tipo del rodamiento	Casquillo de agujas cerrado
Tipo de sellado	No estanco
Especificaciones	Jaula doble
Rodamiento serie	TAM
Unidad de venta	pieza

