

Casquillo de agujas TAMW6050-IKO

TAMW6050-IKO



Shaft dia. mm	Identification number														
	Standard	Mass (Ref. 1) g	Closed end	Mass (Ref. 1) g	Standard	Mass (Ref. 1) g	Closed end	Mass (Ref. 1) g	Grease retained	Mass (Ref. 1) g					
60	TA 6025 Z	158	TAM 6025	182	—	—	—	—	—	—					
	TA 6030 Z	191	TAM 6030	215	—	—	—	—	—	—					
	TA 6040 Z	250	TAM 6040	275	—	—	—	—	—	—					
	TAMW 6045 Z	270	TAMW 6045	295	—	—	—	—	—	—					
	TAMW 6050 Z	306	TAMW 6050	330	—	—	—	—	—	—					
Boundary dimensions mm		Standard mounting dimensions mm						Ball dynamic load rating C	Ball static load rating C ₀	Allowable rotational speed ¹⁾ rpm	Assembled inner ring				
F _w	D	C	j ₂ Max.	Shaft dia. h6				Housing bore dia. H7				N	N		
				Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.				
60	72	25	3.4							54 700	108 000	5 000		IRT 5825	
60	72	30	3.4							66 300	139 000	5 000		IRT 5830	
60	72	40	3.4	60.000	59.981	72.018	71.988	—	—	85 700	163 000	5 000		IRT 5840	
60	72	45	3.4							86 400	163 000	5 000		IRT 5845	
60	72	50	3.4							97 000	229 000	5 000		IRT 5850	



Casquillo de agujas TAMW6050-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	72
C - Espesor (mm)	50
Marca	IKO
Tipo del rodamiento	Casquillo de agujas cerrado
Tipo de sellado	No estanco
Especificaciones	Jaula doble
Rodamiento serie	TAM
Unidad de venta	pieza

