

Casquillo de agujas TAMW7050-IKO

TAMW7050-IKO



Shift no.	Identification numbers									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
70	TA 7025	2181	TAM	7025	215	—	—	—	—	—
	TA 7030	220	TAM	7030	250	—	—	—	—	—
	TA 7014	292	TAM	7040	320	—	—	—	—	—
	TAW 7010	292	TAM	7060	350	—	—	—	—	—

Boundary dimensions mm				Standard mounting dimensions mm				Ball dynamic load rating	Ball static load rating	Allowable rotational speed ¹⁾	Assembled axial clearance		
F_w	D	C	J_2	Shaft hole ϕd		Housing bore dia. ϕD		C'	C_0	n	Δ		
			Max	Min	Min	Max	Min			rpm	mm		
70	82	26	3.4	70.000	99.981	82.022	81.887	—	—	58 500	124 000	3 500	HT 6025
70	82	40	3.4					100	158	50 000	135 000	3 500	HT 6038
70	82	40	3.4					82	100	222 000	3 500	HT 6048	
70	82	50	3.4					105	100	262 000	3 500	HT 6058	



Casquillo de agujas TAMW7050-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	70
D - Diámetro exterior (mm)	82
C - Espesor (mm)	50
Marca	IKO
Tipo del rodamiento	Casquillo de agujas cerrado
Tipo de sellado	No estanco
Especificaciones	Jaula doble
Rodamiento serie	TAM
Unidad de venta	pieza

