

Casquillo de agujas TLAMW2538-IKO
TLAMW2538-IKO


**LE BON
ROULEMENT**



TA...Z TLA...Z TAM TLAM YT YTL

Shaft dia. mm		Identification number									
		Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
25		TLA 2512 Z	19.7	TLAM 2512	23.5	---	---	---	---	---	---
		TLA 2516 Z	26	TLAM 2516	29.5	---	---	---	---	---	---
		TLA 2520 Z	32	TLAM 2520	36	---	---	---	---	---	---
		TLA 2526 Z	41.5	TLAM 2526	45.5	---	---	---	---	---	---
		TLAMW2538Z	58.5	TLAMW2538	62	---	---	---	---	---	---

Boundary dimensions mm		Standard mounting dimensions mm						Basic load rating C ₀	Basic load rating C ₁₀	Allowable rotational speed ¹⁾	Assembled inner ring
		Shaft dia. H6		Housing bore dia. H7 N7							
F _w	D	C	l ₂ Max.	Max.	Min.	Max.	Min.	N	N	rpm	
25	32	12	2.8	---	---	---	---	9 440	13 900	15 000	---
25	32	16	2.8	---	---	---	---	12 900	20 500	15 000	---
25	32	20	2.8	---	---	---	---	16 900	29 300	15 000	WYT 2020-1
25	32	26	2.8	25.000	24.987	---	---	22 600	42 500	15 000	WYT 2026-1
25	32	38	2.8	---	---	31.992	31.987	28 900	58 500	15 000	WYT 2038-1



Casquillo de agujas TLAMW2538-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	32
C - Espesor (mm)	38
Marca	IKO
Tipo del rodamiento	Casquillo de agujas cerrado
Tipo de sellado	No estanco
Especificaciones	Jaula doble
Rodamiento serie	TLAM
Unidad de venta	pieza

