

Casquillo de agujas TLAMW3038-IKO

TLAMW3038-IKO



Shaft dia. mm	Identification number							
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g
30	—	—	—	—	TLA 3020 Z 38	TLAM 3020	43.5	—
	—	—	—	—	TLA 3026 Z 49	TLAM 3026	54.5	—
	—	—	—	—	TLAW3038 Z 69	TLAMW3038	74.5	—

Boundary dimensions mm			Standard mounting dimensions - mm								Basic load rating C _r	Basic load rating C ₀	Allowable rotational speed ¹⁾	Assembled inner ring
F _w	D	C	l ₂ Max.	Shaft dia. h6		Housing bore dia.				N	N	N	rpm	
				Max.	Min.	Max.	Min.	Max.	Min.					
30	37	20	2.8	—	—	—	—	38.992	38.987	18 800	35 100	12 000	RT 2520-1	
30	37	26	2.8	30.000	29.987	—	—	—	—	24 800	50 800	12 000	RT 2526-1	
30	37	38	2.8	—	—	—	—	—	—	31 900	70 200	12 000	RT 2538-1	



Casquillo de agujas TLAMW3038-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	37
C - Espesor (mm)	38
Marca	IKO
Tipo del rodamiento	Casquillo de agujas cerrado
Tipo de sellado	No estanco
Especificaciones	Jaula doble
Rodamiento serie	TLAM
Unidad de venta	pieza

