

Rodillo de apoyo NUKRE35

NUKRE35

**LE BON
ROULEMENT**

NUKR

PWKR 2FS

NUKRE
PWKR 2FS

Designation Designation	Type Designation	Roller height Height (mm)	Roller weight Weight (kg)	Roller weight per unit length (kg/m)	Roller weight Weight (kg)	Dimensions (mm) Dimensions (mm)											
						D	d ₁	d ₂	B	B ₁	B ₂	C	C ₁	i	d ₃	d ₄	d ₅
35	-	-	NUKRE35	177	35	16	52	22.6	29.5	-	18	9.8	5.6	27.6	-	M16x1.5	

Dimensions (mm) Dimensions (mm)		Grease Lubrification	Mounting d ₁	Coefficients de charge Load coefficients				Fatigue limit Fatigue limit	Speed limit Speed limit			
d ₁	d ₂			d ₃	d ₄	d ₅	d ₆					
17	18	20	12	1	NFA287.5	58	15 000	16 000	8 000	16 000	2 220	5 500



Rodillo de apoyo NUKRE35

Caractéristique	Valeur
Roscado	M16X150
Longitud (mm)	52
D - Diámetro exterior (mm)	35
Marca	Genérica alta calidad
Tipo del rodamiento	Rodillo de apoyo de leva de rodillos
Tipo de sellado	No estanco
Especificaciones	Con excéntrico
Rodamiento serie	NUKRE
Tipo de jaula exterior	Jaula exterior abombada
Unidad de venta	pieza

