

Rodillo de apoyo NUKRE52

NUKRE52

**LE BON
ROULEMENT**

NUKRE

PWRL 2FS

PWRE
PWRE-2FS

Designation Designation	Type Designation	Roller height Height (mm)	Roller diameter Diameter (mm)	Roller length Length (mm)	Dimensions (mm) (Dimensions (mm))											
					D	d	B	B ₁	B ₂	C	C ₁	r	d ₁	d ₂	d ₃	d ₄
52	NUKRE52	450	NUKRE52	470	52	20	66	25.6	40.5	9	24	0.8	1	31	4	MUR1.5

Dimensions (mm) (Dimensions (mm))		Coefficient of friction Coefficient of friction	Coefficients of load Coefficients of load				Fatigue limit Fatigue limit	Speed limit Speed limit
d ₁	d ₂		d ₃	d ₄	d ₅	d ₆		
25	10	24	16	1	1	1	1	1



Rodillo de apoyo NUKRE52

Caractéristique	Valeur
Roscado	M20X150
Longitud (mm)	66
D - Diámetro exterior (mm)	52
Marca	Genérica alta calidad
Tipo del rodamiento	Rodillo de apoyo de leva de rodillos
Tipo de sellado	No estanco
Especificaciones	Con excéntrico
Rodamiento serie	NUKRE
Tipo de jaula exterior	Jaula exterior abombada
Unidad de venta	pieza

