

## Rodillo de apoyo NUKRE62

### NUKRE62

**LE BON ROULEMENT**

Designation Designation	Type Designation	Weight (g) Weight (g)	Inner diameter Inner diameter	Weight (g) Weight (g)	Dimensions (mm) Dimensions (mm)											
					D	d	B	B <sub>1</sub>	B <sub>2</sub>	C	C <sub>1</sub>	r	d <sub>1</sub>	A	S	
62	NUKRE62	795	62	804	62	24	80	104	49.5	11	26	1.8	1	38	4	MJ4X1.5

  

Dimensions (mm) Dimensions (mm)		Endplay Endplay	Allowable torque Allowable torque	Coefficients de charge Basic load rating				Charge limite de fatigue Fatigue limit	Viscosité limite Limiting speed				
d <sub>1</sub>	W			dyn. C <sub>10</sub>	stat. C <sub>0</sub>	dyn. F <sub>10</sub>	stat. F <sub>0</sub>						
25	14	38	22	1	WPA3X5.5	220	40 000	50 000	23 500	46 500	6 300	30	2 600



**Rodillo de apoyo NUKRE62**

<b>Caractéristique</b>	<b>Valeur</b>
Roscado	M24X150
Longitud (mm)	80
D - Diámetro exterior (mm)	62
Marca	Genérica alta calidad
Tipo del rodamiento	Rodillo de apoyo de leva de rodillos
Tipo de sellado	No estanco
Especificaciones	Con excéntrico
Rodamiento serie	NUKRE
Tipo de jaula exterior	Jaula exterior abombada
Unidad de venta	pieza

