

# Rodillo de apoyo NUKRE80

## NUKRE80

**LE BON ROULEMENT**

Designation Designation	Type Designation	Weight (g) Weight (g)	Inner diameter Inner diameter	Weight (g) Weight (g)	Dimensions (mm) Dimensions (mm)											
					D	d	B	B <sub>1</sub>	B <sub>2</sub>	C	C <sub>1</sub>	r	d <sub>1</sub>	d <sub>2</sub>	B	
<b>80</b>	<b>NUKRE80</b>	1 600	<b>NUKRE80</b>	1 670	<b>80</b>	30	100	37	63	15	35	1	1.1	47	4	M10x1.5

  

Dimensions (mm) Dimensions (mm)		Endplay Endplay	Mounting Mounting	Coefficients de charge Load coefficients				Fatigue Fatigue	Speed Speed			
d <sub>1</sub>	d <sub>2</sub>			C <sub>10</sub>	C <sub>90</sub>	T <sub>10</sub>	T <sub>90</sub>					
32	14	35	29	1.5	N/A	450	69 000	98 000	47 500	56 000	72 100	1 800



**Rodillo de apoyo NUKRE80**

<b>Caractéristique</b>	<b>Valeur</b>
Roscado	M30X150
Longitud (mm)	100
D - Diámetro exterior (mm)	80
Marca	Genérica alta calidad
Tipo del rodamiento	Rodillo de apoyo de leva de rodillos
Tipo de sellado	No estanco
Especificaciones	Con excéntrico
Rodamiento serie	NUKRE
Tipo de jaula exterior	Jaula exterior abombada
Unidad de venta	pieza

