

Rodillo de apoyo NUKRE90

NUKRE90





Dimension with unit (mm)	Type (designation)	Roller (g) Height (g)	Roller material (material)	Roller (g) Weight (g)	Dimensions (mm) (Dimensions (mm))											
					D	d	B	b	B ₁	b ₁	C	C ₁	i	d ₂	d ₃	S
90	NUKRE90	1 560	NUKRE90	2 020	90	30	100	37	63	15	25	1	1.1	47	4	M08K1.5

Dimensions (mm) (Dimensions (mm))		Coefficient of friction (Coefficient of friction)	Coefficients of load (Coefficients of load)				Fatigue life (Fatigue life)	Speed (Speed)				
d ₁	d ₂		d ₃	d ₄	d ₅	d ₆						
32	14	35	29	1.5	NPA335.5	450	75 000	117 000	77 000	117 000	14 400	1 800



Rodillo de apoyo NUKRE90

Caractéristique	Valeur
Roscado	M30X150
Longitud (mm)	100
D - Diámetro exterior (mm)	90
Marca	Genérica alta calidad
Tipo del rodamiento	Rodillo de apoyo de leva de rodillos
Tipo de sellado	No estanco
Especificaciones	Con excéntrico
Rodamiento serie	NUKRE
Tipo de jaula exterior	Jaula exterior abombada
Unidad de venta	pieza

