

Rodillo de apoyo PWKRE40-2RS-SKF

PWKRE40-2RS-SKF

LE BON ROULEMENT

PWKRE...2RS (PWR...2RS have a concentric collar)

SKF sizes 16 and 19 (SKF, F11, sizes 16 and 19 are with axial sliding rings)

Dimensions														Mass	Designation		
D	C	d	B	B ₂	B ₁	C ₂	d ₂	G	G ₁	M	M ₂	r	SW	c	B ₃	kg	—
mm																	
40	20	22	58	33,5	8	3,8	30	M18x1,5	19	6	3	1	8	1	14	0,26	PWKRE 40,2RS

Designation	Basic load ratings		Fatigue load limit	Maximum radial loads		Limiting speed
	dynamic	static		dynamic	static	
—	C	C ₀	P ₀	F _r	F _{0r}	r/min
PWKRE 40,2RS	13,8	14,3	1,5	13,7	19,6	4 500



Rodillo de apoyo PWKRE40-2RS-SKF

Caractéristique	Valeur
Roscado	M18X150
Longitud (mm)	58
D - Diámetro exterior (mm)	40
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de leva de rodillos
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Especificaciones	Con excéntrico
Rodamiento serie	PWKRE
Tipo de jaula exterior	Jaula exterior abombada
Unidad de venta	pieza

