

Rodillo de apoyo PWKRE80-2RS-SKF

PWKRE80-2RS-SKF

LE BON ROULEMENT

PWKRE...2RS (PWKR...2RS have a concentric collar)

XR, sizes 16 and 19 (XR...19, sizes 16 and 19 are with axial sliding rings)

Dimensions														Mass	Designation		
D	C	d	B	B ₁	B ₂	C ₁	d ₁	G	G ₁	M	M ₂	r min	SW	c	B ₂	kg	—
80	35	35	100	63	15	1	47	M30x1.5	32	8	4	1.5	14	1.5	29	1.67	PWKRE 80.2RS

Designation	Basic load ratings		Fatigue load limit	Maximum radial loads		Limiting speed
	dynamic C	static C ₀		dynamic F _r	static F _{0r}	
—	kN	kN	kN	kN	r/min	—
PWKRE 80.2RS	57,2	73,5	9,3	64	91,5	2000



Rodillo de apoyo PWKRE80-2RS-SKF

Caractéristique	Valeur
Roscado	M30X150
Longitud (mm)	100
D - Diámetro exterior (mm)	80
Marca	SKF
Tipo del rodamiento	Rodillo de apoyo de leva de rodillos
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Especificaciones	Con excéntrico
Rodamiento serie	PWKRE
Tipo de jaula exterior	Jaula exterior abombada
Unidad de venta	pieza

