



Rodamiento de agujas RNAF183012-IKO

RNAF183012-IKO


**LE BON
ROULEMENT**


Shut dia. mm	Identification number	Mass (Ref.) g	Boundary dimensions mm				Standard mounting dimensions mm			Basic load rating C N	Basic static load rating C ₀ N
			F _w	D	C	r _s min	d _b	D _s Max.	D _b		
18	RNAF 182513	23	18	26	13	0.3	21.6	24	18.6	9 330	12 700
	RNAFW 182620	35	18	26	20	0.3	21.6	24	18.6	12 900	19 100
	RNAF 183012	34.5	18	30	12	0.3	23.4	28	18.6	11 800	13 100
	RNAFW 183024	69.5	18	30	24	0.3	23.4	28	18.6	20 200	26 200

Allowable rotational speed (2)
rpm
30 000
30 000
30 000
30 000



Rodamiento de agujas RNAF183012-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	18
D - Diámetro exterior (mm)	30
C - Espesor (mm)	12
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	RNAF
Unidad de venta	pieza

