

Rodamiento de agujas RNAFW183024-IKO

RNAFW183024-IKO

LE BON ROULEMENT

Shut dia. mm	Identification number	Man. (Ref.) b	Boundary dimensions mm				Standard mounting dimensions mm			Bore limits C	Basic static load rating C ₀
			F _w	D	C	r _a (μm)	d _b	D _s Max.	D _b		
18	RNAF 182613	23	18	26	13	0.3	21.6	24	18.6	9 330	12 700
	RNAFW 182620	35	18	26	20	0.3	21.6	24	18.6	12 900	19 100
	RNAF 183012	34.5	18	30	12	0.3	23.4	28	18.6	11 800	13 100
	RNAFW 183024	69.5	18	30	24	0.3	23.4	28	18.6	20 200	26 200

Allowable rotational speed (rpm)

30 000
30 000
30 000
30 000



Rodamiento de agujas RNAFW183024-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	18
D - Diámetro exterior (mm)	30
C - Espesor (mm)	24
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula doble
Rodamiento serie	RNAF
Unidad de venta	pieza

