



Rodamiento de agujas RNAF203212-IKO

RNAF203212-IKO



Shut dia. mm	Identification number	Mass (Ref.) g	Boundary dimensions mm				Standard mounting dimensions mm			Basic load rating C_0 N	Basic static load rating C_{0s} N
			F_w	D	C	$r_{s\ max}$	d_b	D_s Max.	D_b		
20	RNAF 202813	25	20	28	13	0.3	23.6	26	20.6	9 500	13 500
	RNAF 202826	49.5	20	28	26	0.3	23.6	26	20.6	16 400	27 100
	RNAF 203212	37.5	20	32	12	0.3	25.4	30	20.6	12 400	14 300
	RNAFW 203224	75	20	32	24	0.3	25.4	30	20.6	21 200	28 600

Allowable rotational speed ⁽²⁾ rpm
25 000
25 000
25 000
25 000



Rodamiento de agujas RNAF203212-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	32
C - Espesor (mm)	12
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	RNAF
Unidad de venta	pieza

