



Rodamiento de agujas RNAFW223026-IKO

RNAFW223026-IKO


**LE BON
ROULEMENT**


Shut dia. mm	Identification number	Mass (Ref.) g	Boundary dimensions mm				Standard mounting dimensions mm			Basic load rating C N	Basic static load rating C ₀ N
			F _w	D	C	r _a (1)	d _b	D _s Max.	D _b		
22	RNAF 223013	27	22	30	13	0.3	25.6	28	22.6	10 200	15 200
	RNAFW 223026	53.5	22	30	26	0.3	25.6	28	22.6	17 500	30 300
	RNAF 223516	58.5	22	35	16	0.3	27.8	33	22.6	17 600	20 900
	RNAFW 223532	117	22	35	32	0.3	27.8	33	22.6	30 200	41 800

Allowable rotational speed (2)
rpm
25 000
25 000
25 000
25 000



Rodamiento de agujas RNAFW223026-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	22
D - Diámetro exterior (mm)	30
C - Espesor (mm)	26
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula doble
Rodamiento serie	RNAF
Unidad de venta	pieza

