



Rodamiento de agujas RNAF253517-IKO

RNAF253517-IKO


**LE BON
ROULEMENT**


Shut dia. mm	Identification number	Mass (Ref.) g	Boundary dimensions mm				Standard mounting dimensions mm			Basic dynamic load rating C _N	Basic static load rating C ₀
			F _w	D	C	r _s min	d _b	D _s Max.	D _b		
25	RNAF 253517	51	25	35	17	0.3	29.5	33	25.6	17 300	26 600
	RNAF/W 223526	78	25	35	26	0.3	29.5	33	25.6	22 400	37 200
	RNAF 253716	57	25	37	16	0.3	30.4	35	25.6	19 400	24 500
	RNAF/W 253732	114	25	37	32	0.3	30.4	35	25.6	33 200	49 000

Admissible rotational speed (2)
rpm
20 000
20 000
20 000
20 000



Rodamiento de agujas RNAF253517-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	35
C - Espesor (mm)	17
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	RNAF
Unidad de venta	pieza

