



Rodamiento de agujas RNAFW253732-IKO

RNAFW253732-IKO



Shut dia. mm	Identification number	Mass (Ref.) g	Boundary dimensions mm				Standard mounting dimensions mm			Basic load rating C _N	Basic static load rating C ₀
			F _w	D	C	r _a (°)	d _b	D _s Max.	D _b		
25	RNAF 253517	51	25	35	17	0.3	29.5	33	25.6	17 300	26 600
	RNAFW 223526	78	25	35	26	0.3	29.5	33	25.6	22 400	37 200
	RNAF 253716	57	25	37	16	0.3	30.4	35	25.6	19 400	24 500
	RNAFW 253732	114	25	37	32	0.3	30.4	35	25.6	33 200	49 000

Admissible rotational speed (°)
rpm
20 000
20 000
20 000
20 000



Rodamiento de agujas RNAFW253732-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	37
C - Espesor (mm)	32
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula doble
Rodamiento serie	RNAF
Unidad de venta	pieza

