



# Rodamiento de agujas RNAFW304232-IKO

RNAFW304232-IKO



| Shut<br>dia.<br>mm | Identification number | Mass<br>(Ref.)<br>g | Boundary dimensions mm |    |    |                    | Standard mounting<br>dimensions mm |                        |                | Basic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N |
|--------------------|-----------------------|---------------------|------------------------|----|----|--------------------|------------------------------------|------------------------|----------------|--------------------------------|----------------------------------------------------|
|                    |                       |                     | F <sub>w</sub>         | D  | C  | r <sub>a</sub> (°) | d <sub>b</sub>                     | D <sub>s</sub><br>Max. | D <sub>b</sub> |                                |                                                    |
| 30                 | RNAF 304017           | 69                  | 30                     | 40 | 17 | 0.3                | 34.5                               | 38                     | 30.6           | 18 700                         | 31 100                                             |
|                    | RNAFW 304026          | 90.5                | 30                     | 40 | 26 | 0.3                | 34.5                               | 38                     | 30.6           | 24 200                         | 43 400                                             |
|                    | RNAF 304216           | 66                  | 30                     | 42 | 16 | 0.3                | 35.4                               | 40                     | 30.6           | 20 800                         | 28 400                                             |
|                    | RNAFW 304232          | 132                 | 30                     | 42 | 32 | 0.3                | 35.4                               | 40                     | 30.6           | 35 700                         | 56 800                                             |

|                                       |
|---------------------------------------|
| Admissible<br>rotational<br>speed (°) |
| rpm                                   |
| 17 000                                |
| 17 000                                |
| 17 000                                |
| 17 000                                |



**Rodamiento de agujas RNAFW304232-IKO**

| Caractéristique            | Valeur      |
|----------------------------|-------------|
| d - Diámetro interior (mm) | 30          |
| D - Diámetro exterior (mm) | 42          |
| C - Espesor (mm)           | 32          |
| Marca                      | IKO         |
| Tipo del rodamiento        | De agujas   |
| Tipo de sellado            | No estanco  |
| Tipo de jaula              | Acero       |
| Especificaciones           | Jaula doble |
| Rodamiento serie           | RNAF        |
| Unidad de venta            | pieza       |

