



Rodamiento de agujas RNAFW354526-IKO

RNAFW354526-IKO


**LE BON
ROULEMENT**


Shut dia. mm	Identification number	Mass (Ref.) g	Boundary dimensions mm				Standard mounting dimensions mm			Basic load rating C _N	Basic static load rating C ₀
			F _w	D	C	r _a (1)	d _b	D _s Max.	D _b		
25	RNAF 354517	67.5	35	45	17	0.3	39.5	43	35.6	20 500	38 900
	RNAFW 354526	103	35	45	26	0.3	39.5	43	35.6	26 600	51 500
	RNAF 354716	75.5	35	47	16	0.3	40.4	45	35.6	23 100	33 900
	RNAFW 354732	151	35	47	32	0.3	40.4	45	35.6	39 500	67 800

Allowable rotational speed (2)
rpm
14 000
14 000
14 000
14 000



Rodamiento de agujas RNAFW354526-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	35
D - Diámetro exterior (mm)	45
C - Espesor (mm)	26
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Especificaciones	Jaula doble
Rodamiento serie	RNAF
Unidad de venta	pieza

