



# Rodamiento de agujas RNAFW556840-IKO

RNAFW556840-IKO


**LE BON  
ROULEMENT**


| Shul<br>dia.<br>mm | Identification number | Mass<br>(Ref.)<br>g | Boundary dimensions mm |     |     |                  | Standard mounting<br>dimensions mm |               |       | Basic<br>load rating<br>$C$<br>N | Basic static<br>load rating<br>$C_0$<br>N |
|--------------------|-----------------------|---------------------|------------------------|-----|-----|------------------|------------------------------------|---------------|-------|----------------------------------|-------------------------------------------|
|                    |                       |                     | $F_w$                  | $D$ | $C$ | $r_{a\ max}$ (%) | $d_b$                              | $D_s$<br>Max. | $D_b$ |                                  |                                           |
| 55                 | RNAF 556820           | 167                 | 55                     | 68  | 20  | 0.3              | 59.5                               | 66            | 55.8  | 28 600                           | 66 000                                    |
|                    | RNAFW 556840          | 335                 | 55                     | 68  | 40  | 0.3              | 59.5                               | 66            | 55.8  | 49 000                           | 132 000                                   |
|                    | RNAF 557220           | 220                 | 55                     | 72  | 20  | 1                | 60.9                               | 67            | 55.8  | 37 400                           | 66 400                                    |
|                    | RNAFW 557240          | 440                 | 55                     | 72  | 40  | 1                | 60.9                               | 67            | 55.8  | 64 100                           | 133 000                                   |

|                                       |
|---------------------------------------|
| Admissible<br>rotational<br>speed (°) |
| rpm                                   |
| 9 000                                 |
| 9 000                                 |
| 9 000                                 |
| 9 000                                 |



**Rodamiento de agujas RNAFW556840-IKO**

| Caractéristique            | Valeur      |
|----------------------------|-------------|
| d - Diámetro interior (mm) | 55          |
| D - Diámetro exterior (mm) | 68          |
| C - Espesor (mm)           | 40          |
| Marca                      | IKO         |
| Tipo del rodamiento        | De agujas   |
| Tipo de sellado            | No estanco  |
| Tipo de jaula              | Acero       |
| Especificaciones           | Jaula doble |
| Rodamiento serie           | RNAF        |
| Unidad de venta            | pieza       |

