



Rodamiento de agujas NAF102213-IKO

NAF102213-IKO



Shell No.	Identification number	Mass (ref.)	Boundary dimensions - mm					Standard mounting dimensions - mm				
			d	D	C	r _{s max} (°)	F _w	d _h	D _h Max.	d _h Min.	D _h Max.	
10	NAF 102213	26	10	22	13	0.3	14	17.6	20	12	13	14.6
	NAFW 102220	40	10	22	20	0.3	14	17.6	20	12	13	14.6
	NAF 102612	36	10	26	12	0.3	14	19.4	24	12	13	14.6

Ball-bearing load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾	Assembled inner ring
N	N	rpm	
7 850	9 410	35 000	LRT 101413
10 800	14 200	35 000	LRT 101420
9 790	9 880	35 000	LRT 101412



Rodamiento de agujas NAF102213-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	10
D - Diámetro exterior (mm)	22
C - Espesor (mm)	13
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

