



Rodamiento de agujas NAF152813-IKO

NAF152813-IKO



Shell Size	Identification number	Mass (ref.)	Boundary dimensions - mm						Standard mounting dimensions - mm			
			d	D	C	$r_{s\max}$	F_w	d_b	D_b Max.	d_b Min.	D_b Max.	
15	NAF 152813	38.5	15	28	13	0.3	20	23.6	26	17	19	20.6
	NAFW 152826	77.5	15	28	26	0.3	20	23.6	26	17	19	20.6
	NAF 153212	80.5	15	32	12	0.3	20	25.4	30	17	19	20.6

Ball-bearing	Basic static	Allowable	Assembled
load rating	load rating	rotational	inner ring
C	C_0	speed ⁽²⁾	
N	N	rpm	
9 590	13 500	25 000	LRT 152813
16 400	27 100	25 000	LRT 152826
12 400	14 300	25 000	LRT 152912



Rodamiento de agujas NAF152813-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	15
D - Diámetro exterior (mm)	28
C - Espesor (mm)	13
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

