



Rodamiento de agujas NAF173516-IKO

NAF173516-IKO



Shell	Identification number	Mass (ref.)	Boundary dimensions mm						Standard mounting dimensions mm				
mm		g	d	D	C	r_{smax}	r_{wmax}	d_b	D_h Max.	d_h Min.	d_h Max.	D_b	
17	NAF 173013	42.5	17	30	13	0.3	22	25.6	28	19	21	22.6	
	NAFW 173026	84.5	17	30	26	0.3	22	25.6	28	19	21	22.6	
	NAF 173516	77.5	17	35	16	0.3	22	27.8	33	19	21	22.6	
	NAFW 173532	155	17	35	32	0.3	22	27.8	33	19	21	22.6	

Ball-type load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
N	N	rpm	
10 200	15 200	25 000	LRT 172213
17 500	30 300	25 000	LRT 172226
17 600	20 900	25 000	LRT 172216
30 200	41 800	25 000	LRT 172232



Rodamiento de agujas NAF173516-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	35
C - Espesor (mm)	16
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

