



Rodamiento de agujas NAF203517-IKO

NAF203517-IKO



Shell	Identification number	Mod. (ref.)	Boundary dimensions - mm						Standard mounting dimensions - mm				
mm		g	d	D	C	$r_{s\max}$	F_w	d_b	D_b Max.	Min.	d_b Max.	D_b	
20	NAF 203517	74	20	35	17	0.3	25	29.5	33	22	24	25.6	
	NAFW 203526	114	20	35	26	0.3	25	29.5	33	22	24	25.6	
	NAF 203716	79	20	37	16	0.3	25	30.4	35	22	24	25.6	
	NAFW 203732	158	20	37	32	0.3	25	30.4	35	22	24	25.6	

Ball-type load rating C	Basic static load rating C ₀	Allowable rotational speed (°)	Assembled inner ring
N	N	rpm	
17 300	26 600	20 000	LRT 202517
22 400	37 200	20 000	LRT 202526
19 400	24 500	20 000	LRT 202516
33 200	49 000	20 000	LRT 202532



Rodamiento de agujas NAF203517-IKO

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	35
C - Espesor (mm)	17
Marca	IKO
Tipo del rodamiento	De agujas
Tipo de sellado	No estanco
Tipo de jaula	Acero
Rodamiento serie	NAF
Unidad de venta	pieza

